

Appl. No. 10/537,370  
Submission dated June 13, 2007  
Reply to Final Office action of Feb. 13, 2007

**AMENDMENTS TO THE CLAIMS:**

This listing of claims will replace all prior versions and listings of claims in the application:

**Listing of Claims:**

**Claims 1-7. (Canceled)**

8. **(Currently amended)** In a valve for controlling fluids, having a holder body (31) including a receptacle (32) containing a piezoelectric actuator unit (33) and a hydraulic coupler module (34) that has at least one positioning piston and at least one actuating piston (39) that is operatively connected to the positioning piston via a hydraulic coupler (38) and actuates a valve-closure member (27) that cooperates with at least one valve seat (29, 30) and, in the closed position, prevents a flow of fluid from a valve chamber (25) to a return conduit (45), a seal (50) guiding the positioning piston in the receptacle (32), wherein the positioning piston (61) comprises an annular collar (62) and a positioning washer (63) resting against a spring (47), and wherein the seal (50) is disposed between the annular collar (62) and the positioning washer (63).

9. **(Canceled)**

10. **(Canceled)**

Appl. No. 10/537,370  
Submission dated June 13, 2007  
Reply to Final Office action of Feb. 13, 2007

11. **(Previously presented)** The valve according to claim 8, wherein the seal (50) is embodied in the form of an O-ring.

Claims 12-16. **(Canceled)**

17. **(Previously presented)** The valve according to claim 8, characterized in that the receptacle (32) is embodied with a first diameter in the region of the coupler module (34) and with a second diameter that is smaller than the first diameter, and wherein the seal (50) is disposed in the region of the second diameter.

18. **(Canceled)**

19. **(Canceled)**

20. **(Previously presented)** The valve according to claim 11, characterized in that the receptacle (32) is embodied with a first diameter in the region of the coupler module (34) and with a second diameter that is smaller than the first diameter, and wherein the seal (50) is disposed in the region of the second diameter.

21. **(Canceled)**

Appl. No. 10/537,370  
Submission dated June 13, 2007  
Reply to Final Office action of Feb. 13, 2007

22. **(Previously presented)** The valve according to claim 17, wherein an insertion bevel (48) connects the two receptacle regions with different diameters.

23. **(Canceled)**

24. **(Canceled)**

25. **(Previously presented)** The valve according to claim 20, wherein an insertion bevel (48) connects the two receptacle regions with different diameters.

26. **(Canceled)**